

INTRODUCING THE ALL NEW ELECTRIC
INTRAEV
PICKUP
SUCCESS KA MANTRA



1 750 kg
Payload



Long Load Body
2 960 mm (9'8")



Fast Charging from
10% to 80% in
55* min



Electric Power
Assisted Steering



COURIER &
PARCEL



FMCG



E-COMMERCE



WASTE
MANAGEMENT



MILK CANS



LPG
CYLINDER



COLD DRINK
CRATES



*As per ARAI certificate. Under standard driving conditions.

** Range figures are based on real-world driving conditions and may vary depending on load, driving style, terrain, and weather conditions. The illustrations and photographs may show accessories and items of optional equipment which are not part of the standard specifications. Due to printing processes, colours may vary slightly from those shown. All listed specifications are current and subject to change or upgrade without prior notice, in accordance with the company's policy of continuous improvement. *Terms & conditions apply.

Parameter	Intra EV Pickup
Battery Description	28.2 kWh (LFP)
Range (km)	Certified Range as per ARAI - 211* Real World Range - 125 to 140**
Max Power / Motor Output	72 kW / 97 hp
Max Motor Torque	230 Nm
Gradability	23%
Gearbox	Automatic with e-Axle
Steering	EPAS (Electric Power Assisted Steering)
Max Speed (kmph)	80 km/h
Brakes	Front - Disc Brakes & Rear Drum Brakes
Front & Rear suspension	Rigid Suspension with parabolic leaf spring
Tyre	215/75 R15
Seating capacity	D+1
Dimensions	
Length (mm)	4 734 / 4 745
Width (mm)	1 750
Height (mm)	2 010
Wheel Base (mm)	2 600
Ground Clearance (mm)	185
Load body External (mm & ft)	2 960 (9'8") X 1 750 (5'8") X 460 (1'6")
Turning Circle Radius (mm)	6 000
GVW (kg)	3 310
Kerb weight (kg)	1 560
Payload (kg)	1 750
Charging Specifications	
AC Charging time	Fast Charging: 50 min.
AC Charging Type	10.8 – 11 Hrs using 3.3 kW Charger & 4.8 – 5 Hrs using 6.6 kW Charger
DC Fast Charging	(From 10% to 80%) : 50 – 60 Mins - CCS2 Charger
DC Charging Type	CCS2
Warranty (Vehicle)	3 Years or 1 25 000 km* (whichever is earlier)
Warranty (HV Battery)	6 Years or 1 98 000 km* (whichever is earlier)